

Label Shrink Tunnel



Technical Specification :

Model	SP5530L-PE (Shrink Tunnel)
Tunnel Size(WxH) (Mm)	550 x 300
Voltage (V/Hz)	440 /50
Power Consumption (Kw)	24
Conveyor Loading (Kg)	80
Heating Furnace (Mm)	2000 x 550 x 300
Overall Dimension (Mm)	3200 x 710 x 1350
Speed (M/Min.)	0-10
Heating Time (Minutes)	10
Cooling Time (Minutes)	15
Net Weight	320

Shrink Tunnel Machine



Technical Specification :

Model	SPS 3020	SPS	SPS 4535 L	SPS 6535 L
Tunnel Size (W x H) mm	300 x 200	450 x 250	450 x 350	650 x 350
Voltage (V/Hz)	220/50	220/50 -380 / 50	380/50	380/50
Power Consumption (KW)	4.5	6.5	9.6	12.5
Conveyor Loading (Kg)	10	10	30	30
Heating Furnace (l x w x h) mm	900 x 300 x 50-200*	900 x 450 x 50-200*	1200 x 450 x 50-350*	1200 x 650 x 50-350*
External dimensions (l x w x h) (mm)	1200 x 500 x 800	1200 x 650 x 1240	1200 x 650 x 1340	1200 x 850 x 1340
Speed (m/min.)	0~10	0~10	0~10	0~10
Heating Time (minutes)	10	10	10	10
Cooling Time (minutes)	15	15	15	15
Net Weight (Kg)	70	90	120	150

Label Thermal Shrink Packaging Machine



Technical Specification :

Model	SPS 2032
Voltage (V/Hz)	220V /50-60 HZ
Power (kw)	8
Max. Packing Size (I x h) (mm)	120x300
Max Loading (Kg)	15
Dimensions (I x w x h) (mm)	1200x200x350
Tunnel Size (I x w x h) (mm)	2400x450x1150
Conveyor Motor	DC 50 W / 220V
Conveyor Speed	0-10 m/min
Shrink Film	POF, PVC, PP
Weight (Kg)	145

Shrink Chamber



Technical Specifications:

Model	SPSC 5544
Voltage (V/Hz)	AC 220 /50
Power (kw)	4
Packing Speed(pcs/h)	700 ~ 1000
Max Packing Dimensions	500 x 375 x 250
Dimensions (L XW X H) (mm)	1945 x 795 x 1080
Weight (Kg)	80